

Fitting Instructions

General Information



To watch video fitting instructions, please visit: www.hoselink.com.au/help/how-to-videos

For further assistance, please email hello@hoselink.com.au or call **1300 900 617** (M-F 9am – 5pm AEST)

Connector Types

These instructions demonstrate how to fit all connector types across the Hoselink range. Please follow the instructions to match the connectors you have purchased.

Hose End Connectors



Proceed to Step 1

Universal Tap Connector



Proceed to Step 2

Accessory Connectors



Proceed to Step 3



Proceed to Step 5

Step 1

Fit the Hose End Connectors

a. Prepare half a cup of boiling water.



b. Ensure the hose is cut square.



c. Slide yellow nut onto hose & put white split ring flush with hose end.



- d. IMPORTANT! Submerge the hose end 2cm deep into boiled water for approx. 10s to soften.
- e. 1. Hose End Connector: Place the body of the fitting on a hard flat surface & push the hose down firmly, ALL the way to the bottom.



2. Hose Connector with Flow Control: Pull stem out of connector body, place the stem on a hard flat surface & push the hose down firmly, ALL the way to the bottom. Put back into connector body.



Tip: If the hose is not going all the way down, try spraying silicone lubricant onto the stem of the hose end connector and inside the hose.

f. Tighten the yellow nut.



Step 2 Fit Tap Connector _____

Screw tightly onto the tap. If connector appears too small, unscrew size reducer and screw the main connector body onto the tap.





Fit Accessory Connector

Screw directly into the Hoselink sprayer.




Fitting Instructions

Step 4

Connecting it all together

Line up the white markers on each fitting then point and twist together until firmly locked.



Twist to lock until you hear a 'click'

Finished product



Step 5

How to use Hoselink with an Adapter or Convert them to Hoselink _____

To connect to your existing watering accessories, for best results, DON'T use an adapter!

Unscrew the click-on fitting and replace it with an appropriate Hoselink connector.



If you need further help, please watch the following videos: www.hoselink.com.au/help/how-to-videos





Use a Universal Tap Connector 2320 with most pressure washers.





Use an Accessory Connector 2470 with many watering accessories. You may find some products have a molded or glued click-on fitting. If this is the case, you'll need a Click-on Adapter.





This adapter allows you to connect to a click-on type fitting on one end and to a Hoselink Accessory Connector on the other.

For more information on how you can adapt to Hoselink, please visit: www.hoselink.com.au/adapt-to-hoselink

Tips on Using Hoselink

Don't lose O-Rings

Hoselink fittings feature an o'ring to o'ring seal between each connector, which is how they remain watertight. They can be lost if you disconnect fittings under water pressure, so always turn off the water supply and release pressure before disconnecting. Be sure to keep spare o'rings handy, just in case.





How to join hoses

This is easy, just connect one hose end to the other with a point and twist!



My hose is skinny

If the wall of your hose is very thin and you are experiencing leaking, use secateurs to cut a further 2mm off the white split ring. This ensures the split ring can grip tightly around the hose.



How to remove a connector

Follow these steps: Unscrew the yellow nut. Use a small screwdriver in the gap of the white split ring to wedge it back up the hose. Submerge the hose & fitting in boiling water for 10-15 seconds. Remove and drain off the water. Place the fitting between your feet and firmly pull upwards to pull the hose off the barbed stem.



Troubleshooting ———



Please refer to our website for text & video instructions: www.hoselink.com.au/troubleshooting