

INSTALLATION GUIDE Handy Hose Hanger Instructions

ITEM: 4550



Kit Contents

1x Wall unit 1x Door

1x Door hinge pins 3x Screws & plugs

ASSEMBLY

The door may have already been assembled on the unit for postage. If not, set the door into place and push in a hinge pin on either side. You may need to use a hammer or something hard to push them into place.

USING THE HANGER

Store your hose in large loops over the back section of the Wall unit. Store your small watering components and gardening tools in the internal compartment.





INSTALLATION

There are 6 holes in the bracket and 4 screws supplied. Depending on where you are installing the bracket will determine how many and which holes you use to secure it.

If mounting to a wall, use all 4 screws with one at each corner. Alternatively, secure with 2 screws in the top corners only.

If mounting to a post, use 2 screws in the top and bottom centre holes only.

Brick Installation

Tools: Electric drill (hammer or rotary), 10mm masonry drill bit

- 1. Use the Wall unit to mark the 1st hole position.
- 2. Drill the hole with 10mm drill bit, 50mm deep.
- 3. Hammer plug into first hole.
- 4. Now use the Wall unit to mark the 2nd hole position, then drill hole as above and hammer in plug.
- 5. Repeat process if installing other 2 screws.
- 6. Set Wall unit into place, then screw to sec

Timber Installation

Tools: Electric drill, 5mm drill bit

- 1. Use the Wall unit to mark the 2 or 4 hole positions.
- 2. Drill holes with 5mm drill bit, 60mm deep.
- 3. Set Wall unit in place then screw to secu